TIMBERWOLF®

LEAD THE PACK

Timberwolf's range of road towable hydraulic wood chippers are our most popular 'all round' choice. The versatility means they can be used effectively across a range of applications and conditions including landscaping, tree surgery and contract work.

TW 230HB

LIGHTWEIGHT AND POWERFUL

PETROL OR DIESEL CHOICE:

Renowned for its superior performance, reliability, longevity and easy servicing, the TW 230HB range is available with a choice of high-power Briggs and Stratton Vanguard V twin petrol engine or high torque Kubota V1505 diesel engine.

www.timberwolf-uk.com

TIMBERWOLF®
LEAD THE PACK

FEATURES AND BENEFITS:

Lightweight, powerful, and reliable, the TW 230HB range is the best in class:

- Processing throughput of up to 5 tonnes/hr
- 24.8 hp Kubota diesel or 37 hp Briggs and Stratton petrol engine options
- Class-leading 230 mm x 160 mm infeed opening (6 ¼" cutting performance)
- Quad force rollers for ultimate grip, crushing & infeed power
- Sub 750 KG – Lightweight and manoeuvrable
- Dual, ergonomic heavy duty infeed controls
- 280° adjustable discharge chute
- Patented exhaust cooler reduces exhaust temperatures up to 170°C*
- WolfPort blade access and removeable side panels for easy maintenance and servicing accessibility
- Double-sided reversible blades
- Timberwolf reliability and simplicity built-in
- 3-year warranty as standard with optional 5-year extended warranty

TW 230HB SPECIFICATIONS	
PETROL ENGINE	
37 hp Briggs and Stratton (E10 compliant)	
Fuel tank capacity	18 litres
DIMENSIONS	
Weight	710 kg
Height	2177 mm
Height with discharge tube removed	1527 mm
Length (tray down)	3526 mm
Length (tray up)	3022 mm
Width	1520 mm
CHIPPING FEATURES	
Feed method	Twin hydraulic rollers c/w Auto Feed Control
Maximum diameter infeed	160 mm (6 ¼")
Discharge tube	280° adjustable discharge
Blades	2 x 135 mm double sided, fully hardened

TW 230HB SPECIFICATIONS	
DIESEL ENGINE	
24.8 hp Kubota	
Fuel tank capacity	18 litres
DIMENSIONS	
Weight	745 kg
Height	2141 mm
Height with discharge tube removed	1496 mm
Length (tray down)	3766 mm
Length (tray up)	3525 mm
Width	1517 mm
CHIPPING FEATURES	
Feed method	Twin hydraulic rollers c/w Auto Feed Control
Maximum diameter infeed	160 mm (6 ¼")
Discharge tube	280° adjustable discharge
Blades	2 x 135 mm double sided, fully hardened

*Applicable to 230HBP model only